

漆筒印花机

Roller heat transfer machine

(200型)



200*1000/1300



200*1700/1900

机器参数

Machine parameters

多功能标准机配置及参数 (HJD-DP07-01) Multi-function standard machine configuration and parameters		
型号/Model	200×1000/1300	200×1700/1900
电源配置/Power configuration	单项/Single Phase 220V50Hz	单项/Single Phase 220V50Hz
功率/power	6.5KW	9KW
加热方式/Heating method	加热管油温型/Heating tube oil temperature type	加热管油温型/Heating tube oil temperature type
滚筒直径/Drum diameter	200mm	200mm
印花有效面积/Print effective area	1000/1300mm	1700/1900mm
转移产量/Transfer production	0-30m/h	0-30m/h
满油/Full of oil	100%满油/100% full of oil	100%满油/100% full of oil
油箱放置方式/How the tank is placed	外置开放式/Exterior open	外置开放式/Exterior open
油位显示/Oil level display	有/Yes	有/Yes
滚筒涂层/Roller coating	特氟龙/Teflon	特氟龙/Teflon
操作方式/Mode of operation	按钮操作/button actions	按钮操作/button actions
自动开关机/Automatic power on and off	定时关机/Shut down regularly	定时关机/Shut down regularly
毛毡材料/Felt material	30%芳纶70%涤纶, 8mm/30% Nomex, 70% polyester, 8mm	100%芳纶, 8mm/100% Nomex, 8mm
毛毡自动纠偏系统/Felt automatic guiding system	有/Yes	有/Yes
相关尺寸/Relevant dimensions	占地尺寸/Footprint dimensions 1850/2150*1800*1500mm 包装尺寸/Package dimensions 1940/2240*1000*1650mm	占地尺寸/Footprint dimensions :240*2550/2770 *1160 包装尺寸/Package dimensions 整柜2800/3000*1000*1800拼箱2800/3000*1340*1600
重量/Weight	净重/Net weight: 400/450kg , 毛重/Gross weight :480/530kg	净重/Net weight: 900/1100kg , 毛重/Gross weight :1100/1300kg
工作台长度/Table length	1米 (自带铁板)/1m (with built-in iron plate)	1m (需客户自备钢化玻璃/Tempered glass supplied by user:1000*1780/2000*10 一块pc)
轴承加油机/Bearing dispenser	/	便于给加热辊轴承加油延长轴承寿命防止抱死 Easy to add oil to the heating roller bearings to extend their lifespan and prevent them from locking up
导电滑环/Slip Ring	碳刷型升级为一体式集电环, 消除碳刷损耗、积碳、温度跳动异常问题 Upgrade the carbon brush type to an integrated collector ring, eliminating issues such as carbon brush wear, carbon deposition, and abnormal temperature fluctuations	/
压力辊/Pressure roll	无/No	/
自动收卷/Automatic winding	三放两收/ Three releases and two collections	三放两收/Three releases and two collections
200×1000/1300可升级配置 Upgradeable configuration		200×1700/1900可升级配置 Upgradeable configuration
1.气胀轴:收料轴升级为气胀轴 2.防夹手:防止操作人员操作时夹手烫伤 3.触摸屏:按钮控制改为触摸屏控制, 增加7×24小时自动开关机及定温关机等功能 4.兜布槽:布料无需穿轴, 放入滑动槽中即可 5.Wifi功能:连接Wifi功能后可使用手机远程控制 6.独立电箱:电箱独立主机外 延长电器寿命 7.上布纠偏:进料居中, 便于收集 8.面料水冷:厚/特殊面料, 快速降温, 防止变形、污染 9.集烟罩:收集转印过程中油墨升华产生的油雾 1. Inflatable shaft: Upgrade the receiving shaft to an inflatable shaft 2. Anti pinch: prevent operators from getting burned by pinching their hands during operation 3. Touch screen: button control changed to touch screen control, adding functions such as 7 × 24-hour automatic power on/off and constant temperature shutdown 4. Bag groove: The fabric does not need to be threaded, just put it into the sliding groove 5. Wifi function: After connecting to the Wifi function, you can use your phone to remotely control it 6. Independent electrical box: The electrical box extends the service life of electrical appliances by having an independent host outside 7. Correction of upper fabric: The feeding is centered for easy collection 8. Fabric water cooling: Thick/special fabric, fast cooling to prevent deformation and pollution 9. Smoke hood: collects the oil mist generated by ink sublimation during the transfer printing process		1.自动收卷:独立自动收卷机或集成在工作台上, 一步到位不用再上打卷机收卷 2.离合器:手动离合可升级为1.磁粉离合 2.气动离合, 可视化张力调整避免进料褶皱 3.触摸屏:按钮控制改为触摸屏控制, 增加7×24小时自动开关机及定温关机等功能 4.自动分离:毛毡自动张紧自动分离, 减少降温等待时间 5.防夹手:防止操作人员操作时夹手烫伤 6.排烟系统:减少室内转印时产生的油烟 7.安全卡盘:气胀轴安装方便, 可有效防止夹手 8.兜布槽:布料无需穿轴, 放入滑动槽中即可 9.气胀轴:4根铝制:放画纸1根, 收画纸1根, 放衬纸1根, 收衬纸1根 (直径73) 10.Wifi功能:连接Wifi功能后可使用手机远程控制 11.独立电箱:电箱独立主机外 延长电器寿命 12.高低功率切换:满足不同区域客户高低功率需求 13.硅胶辊:铁辊升级为硅胶辊 14.上布纠偏:进料居中, 便于收集 15.面料水冷:厚/特殊面料, 快速降温, 防止变形、污染 16.集烟罩:收集转印过程中油墨升华产生的油雾 1. Automatic winding: an independent automatic winding machine or integrated on the workbench, which can be wound in one step without the need for a winding machine 2. Clutch: Manual clutch can be upgraded to 1. Magnetic powder clutch 2. Pneumatic clutch, visual tension adjustment to avoid feeding wrinkles 3. Touch screen: button control changed to touch screen control, adding functions such as 7 × 24-hour automatic power on/off and constant temperature shutdown 4. Automatic separation: The felt automatically tightens and separates, reducing waiting time for cooling 5. Anti pinch: prevent operators from getting burned by pinching their hands during operation 6. Smoke exhaust system: reduce the oil fume generated during indoor transfer printing 7. Safety chuck: The inflation shaft is easy to install and can effectively prevent hand clamping 8. Bag groove: The fabric does not need to be threaded, just put it into the sliding groove 9. Inflatable shaft: 4 pieces of aluminum: 1 piece for placing drawing paper, 1 piece for collecting drawing paper, 1 piece for placing backing paper, and 1 piece for collecting backing paper (diameter 73) 10. Wifi function: After connecting to Wifi function, you can use your phone to remotely control it 11. Independent electrical box: The electrical box extends the service life of electrical appliances by having an independent host outside 12. High and low power switching: meet the high and low power needs of customers in different regions 13. Silicone roller: Iron roller upgraded to silicone roller 14. Correction of upper fabric: The feeding is centered for easy collection 15. Water cooling of fabrics: Thick/special fabrics, fast cooling to prevent deformation and pollution 16. Smoke hood: collects the oil mist generated by ink sublimation during the transfer printing process