

滚筒织带机
 Narrow fabric sublimation transfer machine



机器参数 / Machine parameters

织带机配置及参数(HJD-DP09) Narrow fabric sublimation transfer machine	
型号/Model	420x600/600x900
电源配置/Power configuration	三相四线 380V50Hz/ Three-phase four-wire 380V50Hz
功率/power	14/27KW
加热方式/Heating method	加热管油温型/Heating tube oil temperature type
滚筒直径/Drum diameter	420/600mm
印花有效面积/Print effective area	600/900mm
满油/Full of oil	100%满油/100% full of oil
油箱放置方式/How the tank is placed	外置开放式/Exterior open
油位显示/Oil level display	有/Yes
滚筒涂层/Roller coating	特氟龙/Teflon
操作方式/Mode of operation	按键控制/Key control
自动开关机/Automatic power on and off	定时关机/Shut down regularly
毛毡材料/Felt material	100%芳纶Nomex, 8mm / 100% Aramid Nomex, 8mm
毛毡自动纠偏系统/Felt automatic guiding system	有/Yes
占地尺寸/Ancient land size	4000*1600*2400mm/4500*2000*2550mm
净重/net weight	1700/2000kg
气胀轴/Air rising shaft	4根铝制:放画纸1根, 收画纸1根, 收衬纸1根, 放衬纸1根(直径 73) 4 pieces of aluminum: 1 piece of drawing paper, 1 piece of drawing paper, 1 piece of backing paper, and 1 piece of backing paper (diameter 73)
轴承加油机/Bearing oiler	便于给加热辊轴承加油延长轴承寿命防止抱死 Easy to add oil to the heating roller bearings to extend their lifespan and prevent them from locking up
压力辊/pressure roller	1 支/pcs
可升级配置 Upgradeable configuration	
防夹手/Anti pinch hands	防止操作人员操作时夹手烫伤/Prevent operators from getting burned by pinching their hands during operation
离合器/clutch	气动离合, 可视化张力调整避免进料褶皱/Pneumatic clutch, visual tension adjustment to avoid feeding wrinkles
触摸屏/touch screen	按钮控制改为触摸屏控制, 增加 7x24 小时自动开关机及定温关机等功能 Change button control to touch screen control, add 7x24 hour automatic power on/off and constant temperature shutdown functions
自动排烟/Automatic smoke exhaust	滚筒自带排烟装置, 降低室内空气污染/The drum comes with a built-in smoke exhaust system to reduce indoor air pollution
自动分离/Automatic separation	毛毡自动张紧自动分离, 减少降温等待时间/ Felt automatically tightens and separates, reducing waiting time for cooling
Wifi功能/Wifi function	连接 Wifi 功能后可使用手机远程控制/ After connecting to the Wifi function, remote control can be achieved using a mobile phone
独立电箱/Independent electrical box	电箱独立主机外 延长电器寿命/Extending the lifespan of electrical appliances outside the independent host of the electrical box
高低功率切换/High and low power switching	满足不同区域客户高低功率需求/Meet the high and low power demands of customers in different regions
硅胶辊/Silicone roller	铁辊升级为硅胶辊 / TUpgrade iron roller to silicon rubber roller
集烟罩/exhaust fume collecting hood	收集转印过程中油墨升华产生的油雾/TCollect the oil mist generated by ink sublimation during the transfer printing process