

2头高端打印机配标准款撒粉机
2-printhead high-end printer with standard powder spreader



机器参数 / Machine parameters

(HJD-S01)2头打印机参数/ Epson i3200-A1*2 Printer parameters


设备类型 Device type	新款2头打印机 New 2 Printhead Printer	喷头型号 Printhead Model	Epson i3200-A1*2颗/pcs
最大打印幅宽 Max print width	65cm	工作环境 Working environment	温度 /Temperature:20°C-28°C 湿度 /Humidity:65-75%
打印精度 Print accuracy	720dpi*1800dpi 6 pass 720dpi*2400dpi 8pass	工作电源 Working power supply	220V 50HZ/60HZ 3.5A
板卡 Control Board	汉森 Hosonssoft	设备占地尺寸 Outside dimensions	1800*780*1700mm L*W*H
RIP软件 RIP software	蒙泰 MainTop	木箱尺寸 Packing size	1950*920*960mm L*W*H
喷头维护 Sprinkler maintenance	自动清洗、自动保湿 Automatic cleaning, automatic moisturizing	重量 The weight of	170kg 木箱重量/Packing weight:210kg
打印速度 Print speed	6pass 8-15㎡/h 8pass 5-12㎡/h	功率 Power	750w
墨水类型及配置 Ink type and configuration	涂料墨水/Pigment ink 青色, 洋红, 黄色, 黑色, 白色 C、M、Y、K、W	可选配置 Optional configuration	可选配cadlink软件/photoprint软件 /printfactory软件/小白印象(XBYX)软件
耗材用量 Consumables usage	白墨/White ink:25ml/平方米/㎡ 彩墨/Color ink:12ml/平方米/㎡ 热熔粉/Hot melt powder:30g/平方米/㎡		

标准撒粉烘干机参数 /Standard Powder Drying Machine Parameters

设备类型 Device type	普通撒粉机(网带款) Standard Powder Drying Machine	搭配机型 Match the model	2头打印机 2 Printhead printer
灯管数量 Number of lamps	5根/pcs	工作电源 Working power supply	AC220V/50Hz 20A
功率 Power	4200W	木箱尺寸 Packed in wooden case size	1830(L)*1080(W)*1250(H)mm
设备占地尺寸 Outside dimensions	2480*1050*1090mm	重量 weight	净重量220kg Net weight 220kg 包装重量280kg Package weight 280kg

机器优势 / Machine advantages


打印机优势 / Advantages of printers

- 

1.X轴铝合金精工加工横梁+亚德客高精度静音导轨, 搭配雷赛一体式步进电机控制, 白彩套色精确到2丝以内
1. X-axis aluminum alloy precision machined crossbeam+Yadeke high-precision silent guide rail, controlled by a Lei Sai integrated stepper motor, and the white color matching is precise to within 2 threads
- 

2. 高强度开模加厚铝合金底座与机头部分牢固结合, 精加工平面度≤0.03, 搭配全铝合金吸风平台组, 提供持久高速高精度打印
2. The high-strength die opening thickened aluminum alloy base is firmly combined with the machine head, with a precision machining flatness of ≤ 0.03. It is matched with an all aluminum alloy suction platform group to provide long-lasting high-speed and high-precision printing
- 

3. 喷头保湿采用免维护一体式升降墨栈, 持久耐用, 保护喷头安全
3. The nozzle moisturizing adopts a maintenance free integrated lifting ink stack, which is durable and protects the nozzle safety
- 

4. 配置缺膜报警停机, 膜用尽时, 电子传感器检测到缺纸状态, 软件报警并停止打印, 防止空打和蹭喷头, 打印机可实现无人值守
4. Configure film shortage alarm shutdown. When the film is exhausted, the electronic sensor detects a paper shortage status, the software alarms and stops printing to prevent empty printing and nozzle rubbing. The printer can achieve unmanned operation
- 

5. 墨盒液位报警系统, 主墨盒墨水不足时蜂鸣器响且对应指示灯亮起, 提示用户添加墨水
5. Ink cartridge level alarm system, when the main ink cartridge is low on ink, the buzzer will sound and the corresponding indicator light will light up, prompting the user to add ink
- 

6. 白墨循环、搅拌系统, 恒金鼎独有的白墨墨壶独立摇晃功能, 无死角充分晃动, 防止白墨沉淀, 畅快生产
6. White ink circulation and stirring system, Hengjinding's unique independent shaking function of white ink pot, fully shaking without dead corners, preventing white ink sedimentation and ensuring smooth production
- 

7. 喷车两侧装有喷头防撞保护系统, 有意外撞击或打印膜刮蹭时迅速停车; 手动按压吸墨装置, 维护墨垫更方便
7. The spray car is equipped with collision protection systems on both sides of the nozzle, which can quickly stop in case of accidental impact or scratching of the printing film; Manually pressing the ink suction device makes it easier to maintain the ink pad
- 

8. 双动力自动放卷配恒张力送膜结构, 高速打印走膜稳定, 保证步进走纸精度; 支持300米大卷打印膜, 批量生产无需频繁换卷, 使用更方便
8. Dual power automatic unwinding with constant expansion force film feeding structure, stable high-speed printing and film feeding, ensuring the accuracy of step-by-step paper feeding; Support 300 meter large roll printing film, batch production does not require frequent roll changes, making it more convenient to use
- 

9.Y轴传动使用进口氟橡胶大压纸轮, 不产生静电, 任意换膜不需要再次调整步进, 保证单面膜走膜稳定不打滑, 不损伤烫画膜打印面
9. The Y-axis drive uses imported fluororubber large paper pressing wheel, which does not generate static electricity. It does not need to adjust the step again to change the film at will, so as to ensure that the single facial mask moves stably without slipping and does not damage the printing surface of the hot stamping film

标准撒粉烘干机优势
Advantages of Standard Powder Drying Machine

- 

1. 标准款智能温控精准, 网带调速, 下粉量可任意调节
1. The standard intelligent temperature control is precise, with mesh belt speed regulation and adjustable powder feeding amount
- 

2. 网带吸风上膜, 方便打样
2. Mesh belt suction film for easy sampling
- 

3. 加大下粉箱无需频繁加粉
3. Increase the powder box without frequent powder addition
- 

4. 自动收卷+前置冷风
4. Automatic winding+front cold air

2头高端打印机配标准款撒粉机
2-printhead high-end printer with standard powder spreader



机器参数 / Machine parameters

(HJD-S01)2头打印机参数/ Epson i3200-A1*2 Printer parameters


设备类型 Device type	新款2头打印机 New 2 Printhead Printer	喷头型号 Printhead Model	Epson i3200-A1*2颗/pcs
最大打印幅宽 Max print width	65cm	工作环境 Working environment	温度 /Temperature:20°C-28°C 湿度 /Humidity:65-75%
打印精度 Print accuracy	720dpi*1800dpi 6 pass 720dpi*2400dpi 8pass	工作电源 Working power supply	220V 50HZ/60HZ 3.5A
板卡 Control Board	汉森 Hosonssoft	设备占地尺寸 Outside dimensions	1800*780*1700mm L*W*H
RIP软件 RIP software	蒙泰 MainTop	木箱尺寸 Packing size	1950*920*960mm L*W*H
喷头维护 Sprinkler maintenance	自动清洗、自动保湿 Automatic cleaning, automatic moisturizing	重量 The weight of	170kg 木箱重量/Packing weight:210kg
打印速度 Print speed	6pass 8-15㎡/h 8pass 5-12㎡/h	功率 Power	750w
墨水类型及配置 Ink type and configuration	涂料墨水/Pigment ink 青色, 洋红, 黄色, 黑色, 白色 C、M、Y、K、W	可选配置 Optional configuration	可选配cadlink软件/photoprint软件 /printfactory软件/小白印象(XBYX)软件
耗材用量 Consumables usage	白墨/White ink:25ml/平方米/㎡ 彩墨/Color ink:12ml/平方米/㎡ 热熔粉/Hot melt powder:30g/平方米/㎡		

标准撒粉烘干机参数 /Standard Powder Drying Machine Parameters

设备类型 Device type	普通撒粉机(网带款) Standard Powder Drying Machine	搭配机型 Match the model	2头打印机 2 Printhead printer
灯管数量 Number of lamps	5根/pcs	工作电源 Working power supply	AC220V/50Hz 20A
功率 Power	4200W	木箱尺寸 Packed in wooden case size	1830(L)*1080(W)*1250(H)mm
设备占地尺寸 Outside dimensions	2480*1050*1090mm	重量 weight	净重量220kg Net weight 220kg 包装重量280kg Package weight 280kg

机器优势 / Machine advantages


打印机优势 / Advantages of printers

- 

1.X轴铝合金精工加工横梁+亚德客高精度静音导轨, 搭配雷赛一体式步进电机控制, 白彩套色精确到2丝以内
1. X-axis aluminum alloy precision machined crossbeam+Yadeke high-precision silent guide rail, controlled by a Lei Sai integrated stepper motor, and the white color matching is precise to within 2 threads
- 

2. 高强度开模加厚铝合金底座与机头部分牢固结合, 精加工平面度≤0.03, 搭配全铝合金吸风平台组, 提供持久高速高精度打印
2. The high-strength die opening thickened aluminum alloy base is firmly combined with the machine head, with a precision machining flatness of ≤ 0.03. It is matched with an all aluminum alloy suction platform group to provide long-lasting high-speed and high-precision printing
- 

3. 喷头保湿采用免维护一体式升降墨栈, 持久耐用, 保护喷头安全
3. The nozzle moisturizing adopts a maintenance free integrated lifting ink stack, which is durable and protects the nozzle safety
- 

4. 配置缺膜报警停机, 膜用尽时, 电子传感器检测到缺纸状态, 软件报警并停止打印, 防止空打和蹭喷头, 打印机可实现无人值守
4. Configure film shortage alarm shutdown. When the film is exhausted, the electronic sensor detects a paper shortage status, the software alarms and stops printing to prevent empty printing and nozzle rubbing. The printer can achieve unmanned operation
- 

5. 墨盒液位报警系统, 主墨盒墨水不足时蜂鸣器响且对应指示灯亮起, 提示用户添加墨水
5. Ink cartridge level alarm system, when the main ink cartridge is low on ink, the buzzer will sound and the corresponding indicator light will light up, prompting the user to add ink
- 

6. 白墨循环、搅拌系统, 恒金鼎独有的白墨墨壶独立摇晃功能, 无死角充分晃动, 防止白墨沉淀, 畅快生产
6. White ink circulation and stirring system, Hengjinding's unique independent shaking function of white ink pot, fully shaking without dead corners, preventing white ink sedimentation and ensuring smooth production
- 

7. 喷车两侧装有喷头防撞保护系统, 有意外撞击或打印膜刮蹭时迅速停车; 手动按压吸墨装置, 维护墨垫更方便
7. The spray car is equipped with collision protection systems on both sides of the nozzle, which can quickly stop in case of accidental impact or scratching of the printing film; Manually pressing the ink suction device makes it easier to maintain the ink pad
- 

8. 双动力自动放卷配恒张力送膜结构, 高速打印走膜稳定, 保证步进走纸精度; 支持300米大卷打印膜, 批量生产无需频繁换卷, 使用更方便
8. Dual power automatic unwinding with constant expansion force film feeding structure, stable high-speed printing and film feeding, ensuring the accuracy of step-by-step paper feeding; Support 300 meter large roll printing film, batch production does not require frequent roll changes, making it more convenient to use
- 

9.Y轴传动使用进口氟橡胶大压纸轮, 不产生静电, 任意换膜不需要再次调整步进, 保证单面膜走膜稳定不打滑, 不损伤烫画膜打印面
9. The Y-axis drive uses imported fluororubber large paper pressing wheel, which does not generate static electricity. It does not need to adjust the step again to change the film at will, so as to ensure that the single facial mask moves stably without slipping and does not damage the printing surface of the hot stamping film

标准撒粉烘干机优势
Advantages of Standard Powder Drying Machine

- 

1. 标准款智能温控精准, 网带调速, 下粉量可任意调节
1. The standard intelligent temperature control is precise, with mesh belt speed regulation and adjustable powder feeding amount
- 

2. 网带吸风上膜, 方便打样
2. Mesh belt suction film for easy sampling
- 

3. 加大下粉箱无需频繁加粉
3. Increase the powder box without frequent powder addition
- 

4. 自动收卷+前置冷风
4. Automatic winding+front cold air