



UV6090平板/圆柱一体机 UV6090 Flat/cylinder integrated machine

机器优势

/ Machine advantages



升降墨栈设计，精准把控封头位置，全方位保护打印头。UV打印绿色环保，色彩鲜艳。
Lift ink stack design, precise control of head position, all-round protection of print head. UV printing is environmentally friendly and has bright colors.



高精度横梁加静音导轨，打印效果更加完美。
High-precision crossbeam with silent guide rails for more perfect printing results.

机器特点 / Machine features

红外线介质超高报警；喷头底板加热；缺墨报警系统；
多重形状材质兼容打印；蜂窝式一体吸风平板；
支持爱普生i3200高位喷射技术（适合打阶梯材质）；
平面及30-120mm直径的圆柱体兼容打印；
彩白油同步输出；光油/哑油/磨砂/烫金工艺先进。

Infrared medium ultra high alarm; Heating of sprinkler bottom plate; Ink shortage alarm system;
Multi-shape material compatible printing; Honeycomb integrated air suction plate;
Support Epson i3200 high injection technology (suitable for ladder material);
Flat and 30-120mm diameter cylinders compatible for printing;
Color white oil synchronous output; Gloss oil/matte oil/scrub/hot stamping echnology advanced.

机器参数 / Machine parameters

产品型号/Product model: HJD-S05						
喷头配置 Sprinkler configuration		爱普生Epson i3200-U1*3颗/pcs	爱普生Epson i3200-U1*4颗/pcs	爱普生Epson F1080-A1*2颗/pcs	墨桶容积 Ink barrel volume	1.5L
产能 Capacity	生产模式 Production mode	720*1800 Dpi / 6pass -7㎡/H	720*1800 Dpi / 6pass -7㎡/H	720*1800 Dpi / 6pass -3㎡/H	工作环境 Working Condition	温度：20~28℃（宜低）；湿度：45%~65%（宜高） Temperature: 20~28℃（should be low); Humidity: 45%~65%（Yigao）
	精度模式 Precision mode	720*2400 Dpi / 8pass -5㎡/H	720*2400 Dpi / 8pass -5㎡/H	720*A400 Dpi / 8pass -2㎡/H		
墨水 ink	中性LED-UV墨水 Neutral LED-UV ink	C/M/Y/K/W /Co 青色/红色/黄色/黑色/ 白色/光油	C/M/Y/K/W/Co 青色/红色/黄色/黑色/ 白色/光油	C/M/Y/K/W/Co 青色/红色/黄色/黑色/ 白色/光油	耗材用量 Consumables usage	普通水晶标 /Common crystal label: 白墨、光油 /White ink &varnish: 25ml/㎡；彩墨 /Colorink: 12ml/㎡； 排废烫金水晶标 /Waste-removable hot stamping crystal label: 白墨 /White ink: 25ml/㎡；彩墨 /Color ink: 12ml/㎡；不沾金、光油、烫金光油 /Anti-stick varnish & hot stamping varnish: 15ml/㎡
	硬性LED-UV墨水 Hard LED-UV ink					
适合材料 Suitable materials		玻璃，板材，各种标牌，水晶，PVC，亚克力，皮革塑料，圆柱形物体（可选装圆柱体打印装置打印）等 Glass, plate, various signs, crystal, PVC, acrylic, leather plastic, cylindrical (object optional cylinder printing device printing), etc			报警系统 Alarm system	墨水报警、行程防护、打印中即时保护 Lack of ink alarm, stroke protection, instant protection in printing
打印方式 Printing method		白墨+彩墨+光油white ink+color ink+gloss oil			最大打印幅宽 Maximum print width	600*900mm
喷头最佳喷射高度 Optimal spray height of the nozzle		1.8mm~3mm（支持12mm高位喷射技术/support 12mm high injection technology）			最高可打印物体厚度 The maximum thickness of the object can be printed	10cm；平台不能调节Platform failure to adjust
RIP软件 RIP software		蒙泰Maintop, Flexi 22(选配/Optional)			固化方式 Curing Method	UV-LED固化灯（风冷式） UV-LED curing lamp(air-cooled type)
板卡 Control Board		汉森/Hosonsoft; 博源恒芯/BYHX			圆柱体治具(选配) Cylinder fixture (optional)	适合圆柱体尺寸：φ30-120mm（不支持光油） Suitable cylinder size: φ 30-120mm (does not support gloss oil)
喷头维护 Sprinkler maintenance		一体式升降墨栈 Integrated lifting ink stack			尺寸 Size	主机尺寸/Host size: 1700*1900*1000mm 包装尺寸/Package dimensions: 2000*1760*1060mm
喷头清洗 Sprinkler cleaning		全自动清洗、全自动刮墨、全自动保湿 Automatic cleaning, automatic scraping, automatic moisturizing			重量 Weight	净重/Net weight: 400kg; 打包重量/Packaged Weight :450kg
供墨系统 Ink supply system		虹吸供墨系统 Siphon ink supply system			电源要求 Power requirements	AC 220V ±5%，50Hz~60Hz 900W
传输接口 Transport interface		USB3.0高速接口/千兆网线 USB3.0 high-speed port/Gigabit network cable			电脑配置 PC configuration	windows 7、8、10 64bit专业版，256G以上固态硬盘、8G主频2400hz以上双通道内存条、2G以上独立显存、酷睿i5处理器（推荐2.8GHz以上频率） windows7、8、10 64bit professional edition, more than 256G SSD, 8G main frequency more than 2400hz dual-channel memory bar, independent dteivco memory above 2G, Core i5 processor (recommended frequency above 2.8GHz)
传动系统 Drivetrain	X轴/X-axis	雷赛步进式一体电机/Reisai stepper integrated motor				
	Y轴/Y-axis	一体式吸风平台/雷赛步进式一体电机/Integrated suction platform/Rayse stepping motor				
	Z轴/Z-axis	1.8~180mm				

UV机可选配设备及工具
Supporting equipment




打印圆柱体装置
Print cylinder device



卷材装置
Coil device



底座
Base



视觉定位
Print cylinder device