

HJD-S08 Weak Solvent Engraving Film Printer

HJD brochure physical page 53: product-specific excerpt



HJD-S08 Weak Solvent Engraving Film Printer

HJD brochure physical page 53: product-specific excerpt

产品型号/Product model : HJD-S08

喷头配置 Sprinkler configuration		爱普生i3200-E1喷头 X2 (可选装4头) Epson i3200-E1 nozzle X 2 (optional 4 heads)	工作环境 Working Condition	温度: 20~28°C (宜低); 湿度: 45%~65% (宜高) Temperature: 20-28 °C (preferably low); Humidity: 45%-65% (preferably high)
墨水ink		八色 (CMYK+LcLmLkLk) 弱溶剂刻字膜墨水/Eco-solvent Heat Transfer Vinyl (HTV) Ink	报警系统 Alarm system	行程防护、喷车防撞、缺墨报警、缺膜报警停机 Travel protection, spray collision prevention, ink shortage alarm, film shortage alarm and shutdown
适合介质 Suitable for media		喷刻打印膜 Spray printing film	最大打印幅宽 Maximum print width	70 cm
产能 (60cm) Capacity	生产模式 (推荐) roduction mode (recommended)	720X1800 Dpi/ 6pass - 10m²/h	特色功能 Featured Features	闲时自动清洗、全色域超细网点ICC、RIPX追色系统 Automatic cleaning during leisure time, full color gamut ultra-fine dot ICC, RIPX color tracking system
	精细模式 Fine mode	720X2400 Dpi / 8pass - 6m²/h		
最佳喷射高度 Optimal spray height		2.0mm	整机功率 Whole machine power	950W
RIP软件 RIP software		蒙泰7.0 / Flexi 22 (选配) / PrintFactory (选配) / 小白印象 (选配) / Cadlink (选配) Montessori 7.0/Flexi 22 (optional)/PrintFactory (optional)/ Little White Impression (optional)/Cadlink (optional)	主机尺寸 Host size	1850*750*1750 mm
喷头维护 Sprinkler maintenance		免维护一体式升降墨栈 Maintenance free integrated lifting ink stack	主机重量 Weight	250KG
喷头清洗 Sprinkler cleaning		全自动清洗、全自动刮墨 Automatic cleaning, automatic scraping	电源要求 Power requirements	两相/Single-phase 220V±5%, 50Hz/60Hz
供墨系统 Ink supply system		虹吸式正负压供墨系统 Siphonic positive and negative pressure ink supply system	电脑配置 PC configuration	操作系统 operating system
传动系统 Drivetrain	X轴 X-axis	雷赛 (杰美康) 步进式一体电机/Airtac直线导轨、静音滑块 Rexay (Jiameikang) stepper integrated motor/Airtac linear guide, silent slider		Windows 7, 8, 10 64bit 专业版 Windows 7, 8, 10 64bit Professional Edition
	Y轴 Y-axis	雷赛 (杰美康) 步进式一体电机/Airtac直线导轨、静音滑块 Rexay (Jiameikang) stepper integrated motor/Airtac linear guide, silent slider		硬件要求 hardware requirements
	墨栈 Ink stack	步进电机 stepping motor		
墨桶容积 Ink barrel volume		500ml	传输接口 Interface	USB2.0接口/千兆网络接口 USB 2.0 interface/Gigabit network interface