

A3 UV DTF Printer

Print and Use Immediately

- ➔ Epson Original Print Head F1080
- ➔ Quantity: 2/3 Units
- ➔ Width: 300mm
- ➔ Color + White + Varnish in One Pass





Stable Machine



System Upgrade



Higher Precision



Higher Efficiency


Printing Speed

Type \ Mode	F1080
Draft	2.4 m ² /h
Production	1.6 m ² /h
Quality	1 m ² /h

Crystal Label Application Solution



Crystal label production steps



Product Technical Specifications

*Specifications and configurations are based on the actual product and may change without prior notice.

Product Model	LC-302U	LC-303U		
Number of Printhead	2	3	Maximum Roll Weight	< 40 kg
Printhead Type	F1080	I3200U1 / I1600 U1/ F1080	Curing System	Air cooled+LED UV lamp
Printhead Height	1-3mm		Laminating rubber roller	High temperature,support gold stamping rubber roller
Printhead Cleaning	Fully automatic cleaning with anti-clogging flashing and automatic moisturizing function		Laminating moving rod	Control the balance of lamination paper feeding
			Receive and release device	Two paper receiving device, two paper releasing device
Ink Type	UV DTF ink		Operation Language	Chinese / English
Ink Color	6 colors (C/M/Y/K/W/V)		Computer System	Win11 / Win10 / Win7
Ink Cartridge Capacity	250ml per color		Working Environment	Temperature range: 18°C-30°C; Humidity range: 40%-60% Rh
Ink Supply Method	Negative pressure continuous ink supply		Printing Interface	network port
Printing Width	300 mm		RIP Software	Maintop
Media	UV DTF AB Film		Power Parameters	AC-220V, 50Hz / 60Hz
Machine Weight	145Kg	165Kg	Power (W)	Standby:32W,Max:1000W
Package Dimensions	1040 * 1040 * 680mm (L * W * H)	1240 * 1240 * 690mm (L * W * H)	Noise Level	Standby <32dB, working ≤65dB